



FLIGHT TERMINATION TRANSMITTER



GENERAL DESCRIPTION

Flight Termination Transmitter, generates flight termination signal in response to commands from the control console or software running on PC. Using this software, the system can be programmed to generate FM flight termination commands according to the assigned IRIG Tones at programmed center frequency. Operating frequency of the system can be set between 390 MHz and 450 MHz.

Compact and portable system can be integrated with HPAs for mobile and fixed ground stations. Also the system has rugged structure to meet harsh environments as well as air and naval platforms.

PC connection is established through RS 232 interface and software automatically connects to the selected serial port of PC. Related Tone A, B, C, D, SAFE, ARM, TERM settings can be done and operating mode can easily be tracked from user friendly GUI running on PC. The system also has Embedded Signal Level Measurement Module option so that users can get feedback from transmitted signal.

TUALFTT is designed to meet RCC 319 Standards. The design of the FTT employs the latest technology and production processes to provide a reliable product with extremely long operating life.


KEY SPECIFICATIONS

- Programmable RF center frequency
- Programmable tone frequencies
- 4 Tone Outputs
- Supports 20 IRIG tones
- MIL-STD-810G Compatible
- Reverse polarity power protection
- Light weight
- Compact size
- RCC 319-14 Compliant

FLIGHT TERMINATION TRANSMITTER




Dimensions (cm)


 7.5 x 6.5 x 1.25

Weight (g)


 108

Frequency Range

 390 - 450 MHz

 **RF Output Power**
Max. 18 dBm (Adjustable)

 **Input Voltage**
18 - 36 VDC

 **Input Current**
Max. 150 mA @ 28 VDC

 **Tone Frequencies**
20 IRIG Tones

 **Programming Interface**
RS232

 **Operating Temperature**
-40 °C to +85 °C

 **Power & I/O Connector**
25-pin Micro-D Socket

 **RF Connectors**
SMA Female

© 2026 TUALCOM: The information contained herein is subject to change without notice. TUALCOM cannot be held responsible for this and no liability is accepted for any errors or omissions.

 TUALCOM

 www.tualcom.com
 sales@tualcom.com
 +90 (312) 485 22 85



150042601